

Power Pack

Specifications



| Model No. | | KPP20-1 | KPP33-1 | KPP50-1 | KPP50-2 | KPP75-1 | KPP75-2 | KPP75-1-230 | KPP75-2-230 | KPP75-3-230 |
|---|-----------------------|------------------------|------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Electrical | Voltage | 120V | 120V | 120V | 120V | 120V | 120V | 230V** | 230V** | 230V** |
| | Frequency | 60 Hz | 60 Hz | 60 Hz | 60 Hz | 60 Hz | 60 Hz | 60 Hz | 60 Hz | 60 Hz |
| | Phase | 1Ø | 1Ø | 1Ø | 1Ø | 1Ø | 1Ø | 1Ø | 1Ø | 1Ø |
| | Electrical Connection | Cord & Plug NEMA 5-20P | Cord & Plug NEMA 5-20P | Hard Wire |
| 120V Single Pump (Models ending ¹ -1') | RLA | 11A | 12.5A | 15.3A | - | 19.6A | - | - | - | - |
| | MCA | 20A | 20A | 20A | - | 25A | - | - | - | - |
| 120V Double Pump (Models ending ¹ -2') | RLA | - | - | - | 21.3A | - | 24.5A | - | - | - |
| | MCA | - | - | - | 25A | - | 30A | - | - | - |
| 230V Single Pump (Models ending ¹ -1-230') | RLA | - | - | - | - | - | - | 11A | - | - |
| | MCA | - | - | - | - | - | - | 20A | - | - |
| 230V Double Pump (Models ending ¹ -2-230') | RLA | - | - | - | - | - | - | - | 14A | - |
| | MCA | - | - | - | - | - | - | - | 20A | - |
| 230V Triple Pump (Models ending ¹ -3-230') | RLA | - | - | - | - | - | - | - | - | 17A |
| | MCA | - | - | - | - | - | - | - | - | 25A |
| Length (A) | | 27" | 27" | 27" | 27" | 27" | 27" | 27" | 27" | 27" |
| Width (B) | | 17" | 17" | 17" | 17" | 20" | 20" | 20" | 20" | 20" |
| Height (C) | | 24-1/2" | 24-1/2" | 24-1/2" | 24-1/2" | 26" | 26" | 26" | 26" | 26" |
| Compressor | | 1/5 HP | 1/3 HP | 1/2 HP | 1/2 HP | 3/4 HP |
| Evaporator Rating @ 15° F (BTUH) | | 1680 | 2600 | 4100 | 4100 | 6950 | 6950 | 6950 | 6950 | 6950 |
| Refrigerant | | R134A | R134A | R134A | R134A | R134A | R134A | R134A | R134A | R134A |
| Cabinet Material | | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel |
| Circulating Pump | | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI | 80 GPH / 100 PSI |
| Reservoir Capacity (gallons) | | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 |
| Refrigerant Charge | | 13 oz. | 14 oz. | 15 oz. | 15 oz. | 20 oz. |
| Glycol Concentration | | 33% | 33% | 33% | 33% | 33% | 33% | 33% | 33% | 33% |

RLA = Rated Load Amps
MCA = Minimum Circuit Ampacity

** 230V models require four wires - 2 hot, 1 neutral, and 1 ground

